



Youtube



视频号



TikTok



GPS



 **YUHUAN DINGLI TOOLS**
玉环鼎力工具

浙江省玉环市楚门镇陈尚工业区虎踞路88号
No. 88, Huhu Road, Yungang Industrial Zone, Chumen Town, Zhejiang, China

☎ 0086-576-87422789

☎ 0086-13666891626 0086-13186936029 (TEL general manager)

☎ 0086-576-87424678

🌐 www.dinglertools.com

✉ info@dinglertools.com



官网/website

 **DINGLI TOOLS**
鼎力工具



www.dinglertools.com



ABOUT US

玉环市鼎力工具有限公司是卡压式管件、滑紧式（冷扩式）管件、空调管等水暖制冷管安装工具的专业制造商，地处中国东海之滨——（中国铜球阀生产基地）玉环。

我们吸纳国际上管压接工具先进的技术，不断地完善、进行产品创新和改良；凭借先进设备、精湛的技术，研发新的产品，让产品设计更合理，安装使用更方便。同时我们公司多款产品获得CE认证及美国市场专利和国内实用新产品专利。

本公司一直以“取诚之道，以质为先，精益求精”作为企业宗旨，注重人才培养和技术改造，严格控制工序过程，完善检测手段，以技术优势和成本优势去赢得市场。我们始终以提高科技含量、加强同客户、市场合作为主要目标，牢固坚定高品质、高效率、同发展、共繁荣的思想意识，努力把企业做大、做强、做优，让“鼎力”成为国内外知名名牌。欢迎国内外贵宾洽谈贸易、技术合作，共同开拓管道安装美好的明天！

Yuhuan Dingli tools factory is a professional manufacturer of crimping tools for different compression fittings, sliding(cold expansion type) pipe fittings, air conditioning pipe fittings and other water heating and refrigeration pipe fittings. It is located in Yuhuan, the coast of the East China Sea (Export and Producing Base of China for Valves, Producing /Purchase Base of China for Water-heating Tools and Valves).

We absorb the most advanced technology of crimping tools for pipes and fittings in the world, and constantly improving and innovating the products. With advanced equipment, exquisite technology, new products are developed to make the product design more reasonable, more convenient for installation. Many products of our company have obtained CE certification, American market patents and domestic utility new product patents.

Our factory always takes "honesty, quality first, excellence" as the enterprise tenet, pays attention to personnel training and technological transformation, strictly controls the procedure of production, and improves testing means, to win the market with technical and cost advantages. We always take improving the content of science and technology, strengthening cooperation with customers and market as the main objective, firmly firm the ideological consciousness of high quality, high efficiency, co-development and co-prosperity, and strive to make the enterprise bigger, stronger and better, so as to make "Dingli" a well-known brand at home and abroad. Welcome the distinguished guests of home and abroad to discuss trade and technical cooperation, and jointly open up a beautiful tomorrow for pipeline installation.



卡压钳系列 CRIMPING TOOLS



DL-1432

- Hand clamp, application range: $\Phi 12, 14, 16, 18, 20, 25(26), 32\text{mm}$
手动卡压钳，适用规格： $\Phi 12, 14, 16, 18, 20, 25(26), 32\text{mm}$
- The head can be rotated 360° so it is suitable for various complicated environment.
头部可 360° 度旋转，适合各种复杂环境下使用
- The length of handles can be extended to 78cm which can save effort when working.
手柄可伸长至 78cm ，工作时更省力
- The molds can be replaceable quickly, press the button then the molds can slide freely.
快速调换模具，按下按钮，模具自由滑动
- Horizontal press: the pressure distribution around the steel sleeve is balanced with the parallel advance of the pressure die, then the crimping effect is better.
平推式压接： $\frac{1}{2}$ 压模平行推进，钢套四周压力分布均衡，压接效果更佳
- Weight: 4kg / 重量： 4kg



DL-1432-A

- Application range: $\Phi 1/2" 3/4" 1" 1\frac{1}{2}, 14, 16, 18, 20, 22, 25(26), 28, 32\text{mm}$ V and H type mold
适用规格： $\Phi 1/2" 3/4" 1" 1\frac{1}{2}, 14, 16, 18, 20, 22, 25(26), 28, 32\text{mm}$ V型和H型模具
- The head can be rotated 360° so it is suitable for various complicated environment.
头部可 360° 度旋转，适合各种复杂环境下使用
- The length of handles can be extended to 78cm which can save effort when working.
手柄可伸长至 78cm ，工作时更省力
- The molds can be replaceable quickly, press the button then the molds can slide freely.
快速调换模具，按下按钮，模具自由滑动
- Horizontal press: the pressure distribution around the steel sleeve is balanced with the parallel advance of the pressure die, then the crimping effect is better.
平推式压接： $\frac{1}{2}$ 压模平行推进，钢套四周压力分布均衡，压接效果更佳
- Weight: 3.6kg / 重量： 3.6kg



DL-1432-B

- Hand clamp, application range: $\Phi 12, 14, 16, 20, 25, 32\text{mm}$
手动卡压钳, 适用规格: $\Phi 12, 14, 16, 20, 25, 32\text{mm}$
- The head can be rotated 360° so it is suitable for various complicated environment.
头部可360度旋转, 适合各种复杂环境下使用
- The handle can be folded in both directions, which makes the initial force more economical, and is more suitable for flexible use in various narrow and small space.
手柄可以双向拆叠, 初始用力时更省力, 且更适合各种狭小空间下灵活使用
- The molds can be replaceable quickly, press the button then the molds can slide freely.
快速调换模具, 按下按钮, 模具自由滑动
- Horizontal press: the pressure distribution around the steel sleeve is balanced with the parallel advance of the pressure die, then the crimping effect is better.
平推式压接: $\frac{1}{2}$ 压模平行推进, 钢套四周压力分布均衡, 压接效果更佳
- Weight: 2.9kg / 重量: 2.9kg



DL-1432-2

- Hand clamp, application range: $\Phi 12, 14, 16, 18, 20, 25(26), 32\text{mm}$
手动卡压钳, 适用规格: $\Phi 12, 14, 16, 18, 20, 25(26), 32\text{mm}$
- The head is flat and short which is more suitable for using in all kinds of narrow space.
头部短且扁平, 更适合各种狭小空间下使用
- The high strength forging process makes the clamp head strong and durable.
高强度锻压制造工艺使钳头坚固耐用
- The length of handles can be extended to 78cm which can save effort when working.
手柄可伸长至78cm, 压接25和32mm时更省力
- Weight: 3.7kg / 重量: 3.7kg



DL-1432-2-A

- Hand clamp, application range: $\Phi 12, 14, 16, 20, 25, 32\text{mm}$
手动卡压钳, 适用规格: $\Phi 12, 14, 16, 20, 25, 32\text{mm}$
- The head is flat and short which is more suitable for using in all kinds of narrow space.
头部短且扁平, 更适合各种狭小空间下使用
- The high strength forging process makes the clamp head strong and durable.
高强度锻压制造工艺使钳头坚固耐用
- Foldable handle
手柄可折叠
- Weight: 2.7kg / 重量: 2.7kg



DL-1432-2-B

- Hand clamp, application range: $\Phi 12, 14, 16, 20, 25, 26\text{mm}$
手动卡压钳, 适用规格: $\Phi 12, 14, 16, 20, 25, 26\text{mm}$
- The head is flat and short which is more suitable for using in all kinds of narrow space.
头部短且扁平, 更适合各种狭小空间下使用
- The high strength forging process makes the clamp head strong and durable.
高强度锻压制造工艺使钳头坚固耐用
- One handle can be foldable
一只手柄可以折叠
- Weight: 2.3kg / 重量: 2.3kg



DL-1420

- Hand clamp, application range: $\Phi 12, 14, 16, 18, 20\text{mm}$
手动卡压钳, 适用规格: $\Phi 12, 14, 16, 18, 20\text{mm}$
- The head is flat and short which is more suitable for using in all kinds of narrow space.
头部短且扁平, 更适合各种狭小空间下使用
- The high strength forging process makes the clamp head strong and durable.
高强度锻压制造工艺使钳头坚固耐用
- Weight: 2.2kg / 重量: 2.2kg



DL-1420-1

- Hand clamp, application range: $\Phi 16, 20\text{mm}$
手动卡压钳, 适用规格: $\Phi 16, 20\text{mm}$
- The head is flat and short which is more suitable for using in all kinds of narrow space.
头部短且扁平, 更适合各种狭小空间下使用
- The high strength steel plate material connection makes the tool lighter and lighter.
高强度钢板材料连接使工具更轻巧
- Weight: 1.5kg / 重量: 1.5kg



DL-1420-2

- Mini hand clamp, application range: $\Phi 12, 14, 16, 18, 20\text{mm}$
迷你形卡压钳, 适用规格: $\Phi 12, 14, 16, 18, 20\text{mm}$
- It is suitable for flexible use in various narrow and small space.
更适合各种狭小空间下灵活使用
- High strength steel stamping is used to the handles which makes the tool more lighter.
手柄采用高强度钢板冲压使工具更轻巧
- Weight: 1.2kg / 重量: 1.2kg



DL-1420-3-A

- Mini hand clamp, application range: $\Phi 12, 14, 16, 18, 20\text{mm}$
迷你形卡压钳, 适用规格: $\Phi 12, 14, 16, 18, 20\text{mm}$
- The handles can be folded in one direction.
手柄可以一边折叠
- High strength steel stamping is used to the handles which makes the tool more lighter.
手柄采用高强度钢板冲压使工具更轻巧
- Weight: 1.3kg / 重量: 1.3kg



DL-1420-3-B

- Mini hand clamp, application range: Φ 12, 14, 16, 18, 20mm
迷你形卡压钳, 适用规格: Φ 12, 14, 16, 18, 20mm
- The handle can be folded in both directions, which makes the initial force more economical, and is more suitable for flexible use in various narrow and small space.
手柄可以双向拆叠, 初始用力时更省力, 且更适合各种狭小空间下灵活使用
- High strength steel stamping is used to the handles which makes the tool more lighter.
手柄采用高强度钢板冲压使工具更轻巧
- Weight: 1.3kg / 重量: 1.3kg



DL-1432-3/4

- Single specification clamp 16mm
单规格卡压钳: 16mm
- Single specification clamp 20mm
单规格卡压钳: 20mm
- There is only one specification for this tool.
一把工具一种规格, 不可替换规格
- Weight: 1.8kg / 重量: 1.8kg



DL-1432-3/4-A

- Single specification clamp 16mm
轻便单规格卡压钳: 16mm
- Single specification clamp 20mm
轻便单规格卡压钳: 20mm
- High strength steel stamping is used to the handles which makes the tool more lighter.
手柄采用高强度钢板冲压使工具更轻巧
- The size of pressure can be adjustable.
可调节压力大小
- Weight: 1.4kg / 重量: 1.4kg



DL-1432-5/6

- Single specification clamp 25mm
单规格卡压钳: 25mm
- Single specification clamp 32mm
单规格卡压钳: 32mm
- There is only one specification for this tool.
一把工具一种规格, 不可替换规格
- Weight: 3.9kg / 重量: 3.9kg



DL-1432-8

- Hydraulic clamp, application range: $\Phi 16, 20, 25(26), 32\text{mm}$
液压卡压钳, 适用规格: $\Phi 16, 20, 25(26), 32\text{mm}$
- Hydraulic power is used to save energy when working
采用液压动力, 工作时更省力
- It is suitable for use in the environment of -10°C to $+40^{\circ}\text{C}$.
适合在 -10°C ~ $+40^{\circ}\text{C}$ 环境内使用
- Weight: 3.5kg / 重量: 3.5kg



DL-1432-9

- Hydraulic clamp application range: $\Phi 16, 20, 25(26), 32\text{mm}$
液压卡压钳, 适用规格: $\Phi 16, 20, 25(26), 32\text{mm}$
- Hydraulic power is used to save energy when working.
采用液压动力, 工作时更省力
- It can be used in the environment of -10°C to $+40^{\circ}\text{C}$.
适合在 -10°C ~ $+40^{\circ}\text{C}$ 环境内使用
- The high strength forging process makes the head of clamp strong and durable.
高强度锻压制造工艺使钳头坚固耐用
- Weight: 3.5kg / 重量: 3.5kg

专利新品
New patented product



DL-1432-9-A

- Manual hydraulic clamp. It can be used for copper and stainless steel pipes
手动液压卡压钳, 适用于铜管不锈钢管
- Application range: $\Phi 1/2" 3/4" 1" 1/2, 14, 16, 18, 20, 22, 25(26), 28, 32\text{mm}$ V and H type mold
适用规格: $\Phi 1/2" 3/4" 1" 1/2, 14, 16, 18, 20, 22, 25(26), 28, 32\text{mm}$ V型和H型模具
- Features: this tool can crimp three kinds of fittings: tee, elbow and direct connection
特色: 一把工具可一次性压接三种管件: 三通, 弯头, 直通
- The high strength forging process makes the head of clamp strong and durable.
高强度锻压制造工艺使钳头坚固耐用
- Weight: 3.5kg / 重量: 3.5kg



DL-4063

- Manual hydraulic large caliper clamp
手动液压大口径卡压钳
- Application range: $\Phi 40, 50, 63, 75\text{mm}$ or $\Phi 16, 20, 25(26), 32, 40, 50, 63, 75\text{mm}$
适用规格: $\Phi 40, 50, 63, 75\text{mm}$ 或 $\Phi 16, 20, 25(26), 32, 40, 50, 63, 75\text{mm}$
- Hydraulic power is used to save energy when working.
采用液压动力, 工作时更省力
- It is suitable for use in the environment of -10°C to $+45^{\circ}\text{C}$.
适合在 -10°C ~ $+45^{\circ}\text{C}$ 环境内使用


DL-4063-A

- Electric hydraulic clamp
电动液压卡压钳
- Application: 16,20,25,32mm U, TH and B type mold
适用规格: 16,20,25,32mm U型, TH型和B型模具
- Charging voltage: 110-240V, frequency: 50Hz
充电电压110-240V, 频率: 50Hz
- It is suitable for use in the environment of -10°C to +45°C.
适合在-10°C - +45°C 环境内使用
- Rechargeable lithium battery, there are three types 18V×2.0Ah/4.0Ah/5.0Ah
充电式锂电池, 规格有18V×2.0Ah/4.0Ah/5.0Ah
- Weight: 4.2kg / 重量: 4.2kg


DL-4063-B

- Electric hydraulic clamp
电动液压卡压钳
- Application: 1/2, 3/4, 1"/15-32mm 适用规格: 1/2, 3/4, 1"/15-32mm
- It can be used for copper and stainless steel pipes
适用于铜管和不锈钢管
- Charging voltage: 110-240V, frequency: 50Hz
充电电压110-240V, 频率: 50Hz
- Rechargeable lithium battery, there are three types 18V×2.0Ah/4.0Ah/5.0Ah
充电式锂电池, 规格有18V×2.0Ah/4.0Ah/5.0Ah
- Weight: 3.8kg / 重量: 3.8kg


DL-4063-C

- Electric hydraulic clamp
电动液压卡压钳
- Application: 16,20,25,32mm 适用规格: 16,20,25,32mm
- Charging voltage: 110-240V, frequency: 50Hz
充电电压110-240V, 频率: 50Hz
- It is suitable for use in the environment of -10°C to +45°C.
适合在-10°C - +45°C 环境内使用
- Rechargeable lithium battery, there are three types 18V×2.0Ah/4.0Ah/5.0Ah
充电式锂电池, 规格有18V×2.0Ah/4.0Ah/5.0Ah
- Weight: 4.8kg / 重量: 4.8kg

专利新品
 New patented product

DL-4063-D

- Electric hydraulic clamp
电动液压卡压钳
- Application range: $\Phi 1/2"$ $3/4"$ $1"$ / 12, 14, 16, 18, 20, 22, 25(26), 28, 32mm V and H type mold
适用规格: $\Phi 1/2"$ $3/4"$ $1"$ / 12, 14, 16, 18, 20, 22, 25(26), 28, 32mm V型和H型模具
- It can be used for copper and stainless steel pipes
适用于铜管和不锈钢管
- Features: this tool can crimp three kinds of fittings: tee, elbow and direct connection
特色: 一把工具可一次性压接三种管件: 三通, 弯头, 直通
- Rechargeable lithium battery, there are three types 18V×2.0Ah/4.0Ah/5.0Ah
充电式锂电池, 规格有18V×2.0Ah/4.0Ah/5.0Ah
- Weight: 4.3kg / 重量: 4.3kg

专利新品
New patented product



DL-4063-B-1

- Large electric clamp
电动大型卡压钳
- Application: $\Phi 16, 20, 25, 26, 32, 40, 50, 63\text{mm}$
适用的规格: $\Phi 16, 20, 25, 26, 32, 40, 50, 63\text{mm}$
- Labor-saving operation: electric clamping, more labor-saving when working.
省力操作: 电动卡压, 工作时更省力。
- Application mold: TH, U, B mold
适用规格: TH, U, B 模具
- Rechargeable lithium battery: 18V*2.0Ah / 4.0Ah/5.0Ah
充电式锂电池: 规格有18V*2.0Ah / 4.0Ah/5.0Ah
- Suitable for use in -10°C — $+45^{\circ}\text{C}$ environment.
适合在 -10°C — $+45^{\circ}\text{C}$ 环境内使用

专利新品
New patented product



DL-1663

- Large electric clamp
电动大型卡压钳
- Application: $\Phi 16, 20, 25, 26, 32, 40, 50, 63\text{mm}$
适用的规格: $\Phi 16, 20, 25, 26, 32, 40, 50, 63\text{mm}$
- Labor-saving operation: electric clamping, more labor-saving when working.
省力操作: 电动卡压, 工作时更省力。
- Application mold: TH, U, B mold
适用规格: TH, U, B 模具
- Rechargeable lithium battery: 18V*2.0Ah / 4.0Ah/5.0Ah
充电式锂电池: 规格有18V*2.0Ah / 4.0Ah/5.0Ah
- Suitable for use in -10°C — $+45^{\circ}\text{C}$ environment.
适合在 -10°C — $+45^{\circ}\text{C}$ 环境内使用



DL-4063-E

- Electric hydraulic large caliper clamp
电动液压大口径卡压钳
- Application range: $\Phi 40, 50, 63, 75\text{mm}$ or $\Phi 16, 20, 25(26), 32, 40, 50, 63, 75\text{mm}$
适用规格: $\Phi 40, 50, 63, 75\text{mm}$ 或 $\Phi 16, 20, 25(26), 32, 40, 50, 63, 75\text{mm}$
- Electric hydraulic power is used, only proofreading position is needed during work.
采用电动液压动力, 工作时只需校对位置
- It is suitable for use in the environment of -10°C to $+45^{\circ}\text{C}$.
适合在 -10°C — $+45^{\circ}\text{C}$ 环境内使用



DL-4063-F

- Manual hydraulic large caliper clamp
手动液压大口径卡压钳
- Application range: $\Phi 40, 50, 63, 75\text{mm}$ or $\Phi 15, 20, 25(26), 32, 40, 50, 63, 75\text{mm}$
适用规格: $\Phi 40, 50, 63, 75\text{mm}$ 或 $\Phi 15, 20, 25(26), 32, 40, 50, 63, 75\text{mm}$
- Electric hydraulic power is used, only proofreading position is needed during work.
采用电动液压动力, 工作时只需校对位置
- It is suitable for use in the environment of -10°C to $+45^{\circ}\text{C}$.
适合在 -10°C — $+45^{\circ}\text{C}$ 环境内使用

DL-1432-10

- Hand clamp, application range: $\Phi 16, 20, 25\text{mm}$
手动卡压钳, 适用规格: $\Phi 16, 20, 25\text{mm}$
- Weight: 1.2kg / 重量: 1.2kg


DL-1432-11

- Hand clamp, application range: $\Phi 16, 20\text{mm}$
手动卡压钳, 适用规格: $\Phi 16, 20\text{mm}$
- It is used for pressing pipes for copper sleeve and aluminum sleeve.
压接铜套, 铝套的卡压管件
- High strength steel plate material makes the tool lighter.
高强度钢板材料连接使工具更轻巧
- Weight: 2.5kg / 重量: 2.5kg


DL-1432-12

- Hand clamp, application range: $\Phi 3/8", 1/2", 3/4", 1"$
手动卡压钳, 适用规格: $\Phi 3/8", 1/2", 3/4", 1"$
- It is used for pressing pipes for copper sleeve and aluminum sleeve.
压接铜套(环), 铝套的卡压管件
- High strength steel plate material makes the tool lighter.
高强度钢板材料连接使工具更轻巧
- Weight: 1.3kg / 重量: 1.3kg


DL-1432-13

- Hand clamp, application range: $\Phi 3/8", 1/2", 3/4", 1", 1-1/2"$
手动卡压钳, 适用规格: $\Phi 3/8", 1/2", 3/4", 1", 1-1/2"$
- It is used for pressing pipes for copper sleeve(ring) and aluminum sleeve.
压接铜套(环), 铝套的卡压管件
- High strength steel plate material makes the tool lighter.
高强度钢板材料连接使工具更轻巧
- Weight: 2.2kg / 重量: 2.2kg



DL-1225

- Small sliding tool
小滑紧工具(适用滑紧管件的安装)
- Application range: $\Phi 12, 16, 20, 25\text{mm}$
适用规格: $\Phi 12, 16, 20, 25\text{mm}$
- It is used for installing S5 series pipes and round teeth fittings.
用于安装S5系列管材, 圆牙管件
- It includes pipe cutter, pipe expander, and sliding tool in one plastic box, which can be used to finish the whole pressing process
此工具集剪管、扩管、推拉于一体, 盒装一套完成全部压接过程
- Weight: 1kg / 重量: 1kg


DL-1225-1

- Small sliding tool
小滑紧工具(适用滑紧管件的安装)
- The body is made of aluminium alloy and feels light when using.
钳体铝合金材质, 手感轻巧
- Application range: $\Phi 12, 16, 20\text{mm}$
适用规格: $\Phi 12, 16, 20\text{mm}$
- It is used for installing S5 series pipes and round teeth fittings.
用于安装S5系列管材, 圆牙管件
- It includes pipe cutter, pipe expander, and sliding tool in one plastic box, which can be used to finish the whole pressing process
此工具集剪管、扩管、推拉于一体, 盒装一套完成全部压接过程
- Weight: 0.6kg / 重量: 0.6kg





DL-1225-2

- Small sliding tool used for wall heating installation
小滑紧工具（墙暖毛细管安装）
- Application range: $\Phi 8, 10\text{mm}$
适用规格: $\Phi 8, 10\text{mm}$
- Weight: 0.9kg / 重量: 0.9kg

专利新品
New patented product



DL-1225-3

- 2 In 1 Sliding Tool+expander
小滑紧工具（适用滑紧管件的安装）
- It is equipped with six pieces of combined expander head to expand the pipe
配有六片组合式扩管头，快速扩管且不破坏管壁
- Application range: $\Phi 16, 20, 25\text{mm}$
适用规格: $\Phi 16, 20, 25\text{mm}$
- It is used for installing S5 series pipes and round teeth fittings.
用于安装S5系列管材、圆牙管件
- It includes pipe expander and sliding tool in one plastic box, which can be used to finish the whole pressing process
此工具集扩管、推拉于一体，盒装一套完成全部压接过程
- Weight: 1kg / 重量: 1kg



DL-1232

- Manual sliding tool
手动滑紧工具（适用滑紧管件的安装）
- Application range: $\Phi 12, 16, 20, 25, 32\text{mm}$ /适用规格: $\Phi 12, 16, 20, 25, 32\text{mm}$
- It is used for installing S5 series pipe and short copper sleeve round tooth fittings.
用于安装S5系列管材、短铜套圆牙管件
- The tool is equipped with the function of inserting pipe, and the installation can be completed without additional tube expansion.
工具自带管材插入管件的功能，不另外扩管也能完成安装工作
- Weight: 3kg / 重量: 3kg



DL-1232-X

- Manual sliding tool
手动滑紧工具（适用滑紧管件的安装）
- Application range: $\Phi 12, 16, 20, 25, 32\text{mm}$
适用规格: $\Phi 12, 16, 20, 25, 32\text{mm}$
- It is used for installing S5 series pipe and short copper sleeve round tooth fittings.
用于安装S5系列管材、短铜套圆牙管件
- Weight: 1.5kg / 重量: 1.5kg

专利新品
New patented product.



DL-1232-T

- Manual sliding tool
手动滑紧工具 (适用滑紧管件的安装)
- Specification: $\Phi 16, 20, 25, 32\text{mm}$ / 适用规格: $\Phi 16, 20, 25, 32\text{mm}$
It is used to install S5 series pipes and short copper sleeve round tooth fittings,
also can be used for S3.2 series, aluminum pipes, S4 series pipes and fittings or
European standard square teeth (Germany Rehau TECE, Watts style) pipes and fittings.
适用于S3.2系列、铝塑管以及S4系列管材、欧标方牙(瑞好款式)或(TECE)、(沃茨)管件。



DL-1232-1-A

- Manual sliding tool
手动滑紧工具 (适用滑紧管件的安装)
- Application range: $\Phi 16, 20\text{mm}$
适用规格: $\Phi 16, 20\text{mm}$
- It is used for installing Prineto pipes and fittings.
用于安装普林多款式管件
- It includes pipe cutter, pipe expander, and sliding tool in one box, which can
complete the whole pressing process.
套装工具集剪管、扩管、推拉于一体, 可完成全部安装过程
- Weight: 1.2kg / 重量: 1.2kg



DL-1232-1

- Application range: $\Phi 16, 20, 25, 32\text{mm}$ / 适用规格: $\Phi 16, 20, 25, 32\text{mm}$
It is used to install S3.2 series, S4 series pipes, (Prineto model) pipes and fittings or
- European standard square teeth (Rehau style).
用于安装S3.2系列、S4系列管材。(普林多款式)管件或欧标方牙(瑞好款式)
- It includes pipe cutter, pipe expander, and sliding tool in one box, which can
complete the whole pressing process.
套装工具集剪管、扩管、推拉于一体, 可完成全部安装过程
- Weight: 2kg / 重量: 2kg



DL-1232-2

- Manual sliding tool with chain
链条手动滑紧工具 (适用滑紧管件的安装)
- Application range: $\Phi 16, 20, 25, 32\text{mm}$
适用规格: $\Phi 16, 20, 25, 32\text{mm}$
- It is used to install S3.2 series, aluminium pipes, S4 series pipes and fittings or
European standard square teeth (Germany Rehau, TECE, Watts style) pipes and fittings.
用于安装S3.2系列、铝塑管及S4系列管材、欧标方牙(德国瑞好款式, TECE, 沃茨)管件
- Sprocket drive torque is adopted, which can save 50% of the traditional
mechanical work.
采用链轮传动扭力, 工作时较传统机械式省力50%
- It includes pipe cutter, pipe expander, and sliding tool in one box, which can
complete the whole pressing process.
套装工具集剪管、扩管、推拉于一体, 可完成全部安装过程
- Weight: 1.8kg / 重量: 1.8kg




DL-1232-3

- Hydraulic sliding tool with expander
液压滑紧工具+扩管器
- Application range: $\Phi 16, 20, 25, 32\text{mm}$
规格: $\Phi 16, 20, 25, 32\text{mm}$
- It can expand the pipe on one side and crimp the pipe and fitting on the other side.
可以一头扩管, 一头压接滑紧管件
- Weight: 2.5kg / 重量: 2.5kg


DL-1232-3-A

- Hydraulic sliding tool with bending handle
弯柄液压滑紧工具 (适用滑紧(冷扩式)管件的安装)
- Specification: $\Phi 16, 20, 25, 32\text{mm}$ 适用规格: $\Phi 16, 20, 25, 32\text{mm}$
- It is used to install S5 series pipes and short copper sleeve round tooth fittings, also can be used for S3.2 series, aluminium pipes, S4 series pipes and fittings or European standard square teeth (Germany Rehau, TECE, Watts style) pipes and fittings.
用于安装S5系列短铜套圆牙管件, 也适用于S3.2系列, 铝塑管及S4系列管材, 欧标方牙(瑞好款式)或(普林多款式)管件。(TECE)(沃茨)管件
- The molds both can be pressed and rotated 360° and is more suitable for using in small space and wall corner cracks.
弯柄T字型液压滑紧工具, 可以多角度旋转压接方向(二个地方可360°转向), 更适合狭小空间和墙角夹缝里使用。
- Hydraulic power is used to save energy when working. 采用采用液压动力, 工作时更省力
- It includes pipe cutter, pipe expander, and sliding tool in one box, this set can complete the whole pressing process.
套装工具集剪管、扩管、推拉于一体, 盒装一套可完成全部安装过程
- Weight: 2kg / 重量: 2kg


DL-1232-3-C

- Hydraulic sliding tool with bending handle
三合一滑紧工具 (适用滑紧(冷扩式)管件的安装)
- Specification: $\Phi 16, 20, 25\text{mm}$ 适用规格: $\Phi 16, 20, 25\text{mm}$
- It is used to install S5 series pipes and short copper sleeve round tooth fittings, also can be used for S3.2 series, aluminium pipes, S4 series pipes and fittings or European standard square teeth (Germany Rehau, TECE, Watts style) pipes and fittings.
适用于S3.2系列, 铝塑管及S4系列管材, 欧标方牙(瑞好款式)或(TECE), (沃茨)管件
- The advantage of this tool is the integration of 16, 20 and 25 three specifications, which is more convenient to use. 此工具最大优点是16, 20, 25三个规格融为一体, 使用更方便
- Hydraulic power is used to save energy when working. 采用液压动力, 工作时更省力
- It includes pipe cutter, pipe expander, and sliding tool in one box, the whole set can complete the whole pressing process.
套装工具集剪管、扩管、推拉于一体, 盒装一套可完成全部安装过程
- Weight: 2.1kg / 重量: 2.1kg

专利新品
 New patented product

DL-1232-3-C-A

- Hydraulic Sliding Tool With Bending Handle
三合一液压滑紧工具
- Specification: $\Phi 16, 20, 25\text{mm}$
适用规格: $\Phi 16, 20, 25\text{mm}$
- It is used to install S5 series pipes and short copper sleeve round tooth fittings, also can be used for S3.2 series, aluminium pipes, S4 series pipes and fittings or European standard square teeth (Germany Rehau TECE, Watts style) pipes and fittings.
适用于S3.2系列, 铝塑管以及S4系列管材, 欧标方牙(瑞好款式)或(TECE), (沃茨)管件。
- It can rotate and press the joint direction at multiple angles (360 degrees) is more suitable for use in narrow space and wall corner cracks.
T字型液压滑紧工具, 可以多角度旋转压接方向更适合狭小空间和墙角夹缝里使用。
- The advantage of this tool is the integration of 16, 20 and 25 three specifications, which is more convenient to use, and the head of expander include 16, 20, 25mm
此工具最大点是将16, 20, 25三个规格融为一体, 使用更方便, 而且单个扩管头融合了16, 20, 25mm三个尺寸。
- The advantage of this tool is the integration of 16, 20 and 25 three specifications, which is more convenient to use. 此工具最大优点是16, 20, 25三个规格融为一体, 使用更方便
- Hydraulic power is used to save energy when working.
采用液压动力, 工作时更省力。
- It includes pipe cutter, pipe expander, and sliding tool in one box, the whole set can complete the whole pressing process.
套装工具集剪管、扩管、推拉于一体, 盒装一套可完成全部安装过程





DL-1232-3-B

- Hydraulic sliding tool with bending handle which is suitable for installation of sliding pipes and fittings (cold expansion)
- 弯柄液压滑紧工具 (适用滑紧 (冷扩式) 管件的安装)
- Specification: $\Phi 16, 20, 25, 32\text{mm}$ 适用规格: $\Phi 16, 20, 25, 32\text{mm}$
- It is used to install S5 series pipes and short copper sleeve round tooth fittings, also can be used for S3.2 series, aluminium pipes, S4 series pipes and fittings or European standard square teeth (Germany Rehau, TECE, Watts style) pipes and fittings. 适用于S3.2系列、铝塑管及S4系列管材、欧标方牙(瑞好款式)、(TECE)、(沃茨)管件
- It can rotate and press the joint direction at multiple angles (360 degrees in two places), is more suitable for use in narrow space and wall corner cracks.
- 弯柄7字型液压滑紧工具, 可以多角度旋转压接方向(二个地方可360°转向), 更适合狭小空间和墙角夹缝里使用
- Hydraulic power is used to save energy when working. 采用液压动力, 工作时更省力
- It includes pipe cutter, pipe expander, and sliding tool in one box, which can complete the whole pressing process. 套装工具集剪管、扩管、推拉于一体, 盒装一套可完成全部安装过程
- Weight: 2kg / 重量: 2kg

所配扩管器形状不同, 分二种不同形状的塑盒包装

The shape of expander in these two sets are different, so the shape of the plastic box also is different, see the following pictures:



DL-1232-3-B-(1)

DL-1232-3-B-(2)

二种形状扩管器的扩管头不可通用

The heads of two kinds of expander are not universal



Curved shank expander
18° taper, cap shape

Straight shank expander
20° taper, cap shape

专利新品
New patented product

DL-1232-3-B-A



- Hydraulic Sliding Tool With Bending Handle
复合型扩管头
- Specification: $\Phi 16, 20, 25\text{mm}$
适用规格: $\Phi 16, 20, 25\text{mm}$
- It is used to install S5 series pipes and short copper sleeve round tooth fittings, also can be used for S3.2 series, aluminium pipes, S4 series pipes and fittings or European standard square teeth (Germany Rehau TECE, Watts style) pipes and fittings. 适用于S3.2系列、铝塑管以及S4系列管材、欧标方牙(瑞好款式)或(TECE)、(沃茨)管件
- It can rotate and press the joint direction at multiple angles (360 degrees) is more suitable for use in narrow space and wall corner cracks. 7字型液压滑紧工具, 可以多角度旋转压接方向更适合狭小空间和墙角夹缝里使用
- The advantage is the integration of 16, 20, 25, 32 four specifications, which is more convenient to use. The head of expander include 16, 20mm or 20, 25mm or 25, 32mm
- 此工具最大优点是融合了16, 20, 25, 32四个尺寸, 使用更方便, 而且你可以选择三个不同尺寸的头例如: 16, 20mm; 20, 25mm; 25, 32mm
- Hydraulic power is used to save energy when working. 采用液压动力, 工作时更省力
- It includes pipe cutter, pipe expander and sliding tool in one box, the whole set can complete the whole pressing process. 套装工具集剪管、扩管、推拉于一体, 盒装一套可完成全部安装过程



DL-1232-3-D

- Large diameter hydraulic sliding tool
大口径液压滑紧工具
- Specification: $\Phi 32, 40, 50\text{mm}$ 适用规格: $\Phi 32, 40, 50\text{mm}$
- It includes pipe expander and sliding tool in one box, which can complete the whole pressing process. 套装工具集扩管、推拉于一体, 可完成全部安装过程
- Weight: 14.5kg / 重量: 14.5kg


DL-1232-3-E

- Hydraulic sliding tool+Electric expander
液压滑紧工具+电动扩管器
- Specification: $\Phi 32,40\text{mm}$ 适用规格: $\Phi 32,40\text{mm}$
It is used to install S5 series pipes and short copper sleeve round tooth fittings, also can be used for S3.2 series, aluminium pipes, S4 series pipes and fittings or European standard square teeth (Germany Rehau, TECE, Watts style) pipes and fittings. 用于安装S3.2系列、铝塑管及S4系列管材、欧标方牙(瑞好款式)或(TECE)、(沃茨)管件。
- It includes pipe expander and sliding tool in one box, which can complete the whole pressing process.
套装工具集扩管、推拉于一体,可完成全部安装过程
- Weight: 5.0kg / 重量: 5.0kg

专利新品
New patented product


DL-1232-3-G

- Electric hydraulic sliding tool
电动液压滑紧工具
- Specification: $\Phi 16,20,25,32\text{mm}$ 适用规格: $\Phi 16,20,25,32\text{mm}$
It is used to install S5 series pipes and short copper sleeve round tooth fittings, also can be used for S3.2 series, aluminium pipes, S4 series pipes and fittings or European standard square teeth (Germany Rehau, TECE, Watts style) pipes and fittings. 适用于S3.2系列、铝塑管及S4系列管材、欧标方牙(瑞好款式)、(TECE)、(沃茨)管件。
- It can rotate and press the joint direction at multiple angles (360 degrees in two places), is more suitable for use in narrow space and wall corner cracks.
弯柄7字型液压滑紧工具,可以多角度旋转压接方向(二个地方可360°转向),更适合狭小空间和墙角夹缝里使用
- Weight: 3.7kg / 重量: 3.7kg



专利新品
New patented product


DL-1232-3-H

- Electric hydraulic sliding tool
电动液压滑紧工具
- Specification: $\Phi 16,20,25,32\text{mm}$ 适用规格: $\Phi 16,20,25,32\text{mm}$
It is used to install S5 series pipes and short copper sleeve round tooth fittings, also can be used for S3.2 series, aluminium pipes, S4 series pipes and fittings or European standard square teeth (Germany Rehau, TECE, Watts style) pipes and fittings. 用于安装S5系列短铜套圆牙管件,也适用于S3.2系列、铝塑管及S4系列管材、欧标方牙(瑞好款式)或(普林多款式)管件、(TECE)(沃茨)管件
- The molds both can be pressed and rotated 360° and is more suitable for using in small space and wall corner cracks.
弯柄7字型液压滑紧工具,可以多角度旋转压接方向(二个地方可360°转向),更适合狭小空间和墙角夹缝里使用。
- Weight: 4.0kg / 重量: 4.0kg



专利新品
New patented product


DL-1232-3-K

- Electric Axial Press & Expand Tool
二合一滑紧和扩管复合型电动工具
- Specification: $\Phi 16,20,25,32\text{mm}$ 适用规格: $\Phi 16,20,25,32\text{mm}$
It is used to install S5 series pipes and short copper sleeve round tooth fittings, also can be used for S3.2 series, aluminium pipes, S4 series pipes and fittings or European standard square teeth (Germany Rehau, TECE, Watts style) pipes and fittings. 适用于S3.2系列、铝塑管以及S4系列管材、欧标方牙(瑞好款式)或(TECE)、(沃茨)管件。
- It can rotate and press the joint direction at multiple angles, include press and expand, more convenient.
可以多角度旋转压接方向更方便。

专利新品
New patented product



DL-1232-3-I

- Electric Hydraulic Sliding Tool
二合一电动液压滑紧加扩管工具
- Application range: $\Phi 16, 20, 25, 32\text{mm}$
适用范围: $\Phi 16, 20, 25, 32\text{mm}$
- Specification: $\Phi 16, 20, 25, 32\text{mm}$ 适用规格: $\Phi 16, 20, 25, 32\text{mm}$
- It is used to install S5 series pipes and short copper sleeve round tooth fittings, also can be used for S3.2 series, aluminum pipes, S4 series pipes and fittings or European standard square teeth (Germany Rehau TECE, Watts style) pipes and fittings.
适用于S3.2系列、铝塑管以及S4系列管材、欧标方牙(瑞好款式)或(TECE)、(沃茨)管件。
- It can expand the pipe on the one side and crimp the pipe and fitting on the other side.
可以一头电动扩管, 一头电动液压接滑紧管件。



DL-2040

- Large Electric Expanding and Sliding Tool
电动大型扩管滑紧二合一工具
- Application: $\Phi 20, 25, 32, 40\text{mm}$
适用的规格: $\Phi 20, 25, 32, 40\text{mm}$
- Labor-saving operation: electric slip tight, battery power, more labor-saving when working.
省力操作: 电动滑紧, 电池动力大, 工作时更省力。
- One machine for two purposes, one end of the tube, One end of the slide tight.
一机两用, 一头扩管, 一头滑紧。
- Rechargeable lithium battery: 18V*2.0Ah / 4.0Ah/5.0Ah
充电式锂电池: 规格有18V*2.0Ah / 4.0Ah/5.0Ah
- Suitable for use in -10°C — $+45^{\circ}\text{C}$ environment.
适合在 -10°C — $+45^{\circ}\text{C}$

专利新品
New patented product



DL-1232-3-L

- Electric hydraulic sliding tool + Electric expander
电动液压滑紧工具 + 电动扩管
- Specification: $\Phi 25 32 40 50\text{mm}$ 适用规格: $\Phi 25 32 40 50\text{mm}$
- It is used to install S5 series pipes and short copper sleeve round tooth fittings, also can be used for S3.2 series, aluminium pipes, S4 series pipes and fittings or European standard square teeth (Germany Rehau, TECE, Watts style) pipes and fittings.
适用于S3.2系列、铝塑管及S4系列管材、欧标方牙(瑞好款式)、(TECE)、(沃茨)管件
- It can rotate and press the joint direction at multiple angles (360 degrees in two places), is more suitable for use in narrow space and wall corner cracks.
弯柄7字型液压滑紧工具, 可以多角度旋转压接方向(二个地方可360°转向), 更适合狭小空间和墙角夹缝里使用
- Weight: 4.5kg / 重量: 4.5kg



DL-1232-3-M

- Large diameter electric hydraulic sliding tool
大口径电动液压滑紧工具
- Specification: $\Phi 40 50 63\text{mm}$ 适用规格: $\Phi 40 50 63\text{mm}$
- It includes pipe expander and sliding tool in one box, which can complete the whole pressing process.
套装工具集扩管、滑紧于一体, 可完成全部安装过程


DL-1232-4

- Manual sliding tool
手动滑紧工具 (适用滑紧管件的安装)
- Specification: $\Phi 16, 20, 25, 32\text{mm}$ 适用规格: $\Phi 16, 20, 25, 32\text{mm}$
- It is used to install S5 series pipes and short copper sleeve round tooth fittings, also can be used for S3.2 series, aluminium pipes, S4 series pipes and fittings or European standard square teeth (Germany Rehau, TECE, Watts style) pipes and fittings.
用于安装S3.2系列、铝塑管及S4系列管材、欧标方牙(瑞好款式)或(TECE)、(沃茨)管件
- It includes pipe cutter, pipe expander, and sliding tool in one box, which can complete the whole pressing process.
套装工具集剪管、扩管、推拉于一体, 可完成全部安装过程
- Weight: 3kg / 重量: 3kg


DL-1232-5

- Pedal hydraulic sliding tool
脚踏式液压滑紧工具 (适用滑紧(冷扩式)管件的安装)
- Specification: $\Phi 16, 20, 25, 32\text{mm}$ 适用规格: $\Phi 16, 20, 25, 32\text{mm}$
- It is used to install S5 series pipes and short copper sleeve round tooth fittings, also can be used for S3.2 series, aluminium pipes, S4 series pipes and fittings or European standard square teeth (Germany Rehau, TECE, Watts style) pipes and fittings.
适用于S3.2系列、铝塑管及S4系列管材、欧标方牙(瑞好款式)、(TECE)、(沃茨)管件
- Hydraulic power is used to save energy when working. 采用液压动力, 工作时更省力
- It includes pipe cutter, pipe expander, and sliding tool in one box, the whole set
套装工具集剪管、扩管、推拉于一体, 套装一套可完成全部安装过程
- Weight: 7kg / 重量: 7kg


DL-1232-6

- Manual sliding tool
手动滑紧工具 (适用于专用滑紧管件的安装)
- Specification: $\Phi 16, 20, 25, 32\text{mm}$ 适用规格: $\Phi 16, 20, 25, 32\text{mm}$
- It is suitable for the installation of aluminum plastic pipes and special fittings.
适用安装铝塑管及专用管件
- The tool is equipped with the function of inserting pipe, and the installation can be completed without additional lube expansion.
工具自带管材插入管件的功能, 一把工具可完成整套安装过程
- Weight: 1.2kg / 重量: 1.2kg


DL-1232-3-F

- Sliding tool for copper pipe
铜管(空调管)滑紧工具
- Specification: $\Phi 9-25\text{mm}$
适用规格: $\Phi 9-25\text{mm}$
- It is suitable for installation of copper pipes and fittings.
适用于铜管冷挤压管件的安装
- Weight: 3.3kg / 重量: 3.3kg



DL-1232-7

- Manual expander with straight handle
直柄手动扩管器
- With the matched size heads of expander, press the handle lightly which can expand the pipe quickly. 配上扩管头轻压手柄可快速扩涨管子
- The handle is die-casting aluminium alloy handicraft, high strength, no fracture and light weight.
压铸铝合金工艺手柄, 强度高, 不断裂且重量轻
- Weight: 0.7kg / 重量: 0.7kg



DL-1232-8

- Manual expander with curved handle
弯柄手动扩管器
- With the matched size heads of expander, press the handle lightly which can expand the pipe quickly.
配上扩管头轻压手柄可快速扩涨管子
- The handle is die-casting aluminium alloy handicraft, high strength, no fracture and light weight.
压铸铝合金工艺手柄, 强度高, 不断裂且重量轻
- Weight: 0.7kg / 重量: 0.7kg



DL-1232-7-A

- Electric Expander
电动扩管器
- Special tool for Uponor pipes and fittings.
快易环(快插式管件)专用工具
- It is suitable for Uponor pipes and fittings 16*1.8(2.0), 20*1.9(2.0), 25*2.3, 32*2.9mm. Also suitable for GIACOMINI 16*2.2, 20*2.8mm.
- 适合“欧博诺”款式管件16*1.8(2.0), 20*1.9(2.0), 25*2.3, 32*2.9也适合“嘉科米尼”16*2.2, 20*2.8
- Specification: $\Phi 16, 20, 25, 32\text{mm}$ and $\Phi 1/2", 3/4", 1"$
适用规格: 英制 $\Phi 1/2", 3/4", 1"$, 公制 $\Phi 16, 20, 25, 32\text{mm}$
- Rechargeable lithium battery, equipped with 12V x 1.5Ah and 12V x 3.0Ah two batteries, it is safe, reliable and easy to carry and use.
充电式锂电池, 配有12V*1.5Ah, 12V*3.0Ah二块电池, 安全可靠且携带使用很方便
- In the process of pipe expanding, the head expands and rotates together automatically, and the wall of pipe can be evenly distributed and extended around, so there will be no crack in the pipe's wall.
扩管过程中, 头部自动边扩大边旋转方向, 管壁周围可均匀分布扩开, 管壁没有裂痕
- Weight: 1.5kg / 重量: 1.5kg



专利新品
Patented New Product



DL-1640

- Electric Expander (16-40mm)
电动扩管器
- Specification: $\Phi 16, 20, 25, 32, 40\text{mm}$ and $\Phi 1/2", 3/4", 1", 1-1/4", 1-1/2"$
英制 $\Phi 1/2", 3/4", 1", 1-1/4", 1-1/2"$, 公制 $\Phi 16, 20, 25, 32, 40\text{mm}$
- Uponor pipes and fittings.
快易环(快插式管件)专用工具
- It is suitable for Uponor pipes and fittings 16*1.8(2.0), 20*1.9(2.0), 25*2.3, 32*2.9, 40*3.7mm. Also suitable for GIACOMINI 16*2.2, 20*2.8, 25*3.5, 32*4.4
- 适合“欧博诺”式管件16*1.8(2.0), 20*1.9(2.0), 25*2.3, 32*2.9, 40*3.7mm, 也适合“嘉科米尼”16*2.2, 20*2.8, 25*3.5, 32*4.4
- Rechargeable lithium battery, equipped with 22Vx3.0Ah.
充电式锂电池, 配有两块22Vx3.0Ah电池, 安全可靠且携带使用方便
- In the process of pipe expanding, the head expands and rotates together automatically, and the wall of pipe can be evenly distributed and extended around, so there will not be crack in the pipe's wall.
扩管过程中, 头部自动边扩大边旋转方向, 管壁周围可均匀分开扩开, 管壁没有裂痕



DL-1232-8-1

- Manual expander for copper tube
铜管专用扩管器
- Specification: $\Phi 3/8'' \sim 1-1/8''$
适用规格: $\Phi 3/8'' \sim 1-1/8''$
- With the matched size heads of expander, press the handle lightly, which can expand the pipe quickly.
配上扩管头轻压手柄可快速扩涨管子
- The handle is die-casting aluminium alloy handicraft, high strength, no fracture and light weight.
压铸铝合金工艺手柄, 强度高, 不断裂且重量轻
- Weight: 0.7kg / 重量: 0.7kg



DL-1232-8-2

- Manual hydraulic expander for copper tube
液压扩管器, 铜管专用
- Specification: $\Phi 3/8'' \sim 1-1/8''$
适用规格: $\Phi 3/8'' \sim 1-1/8''$
- With the matched size heads of expander press the handle lightly can expand the pipe quickly.
配上扩管头轻压手柄可快速扩涨管子
- The handle is die-casting aluminium alloy handicraft, high strength, no fracture and light weight.
压铸铝合金工艺手柄, 强度高, 不断裂且重量轻
- Weight: 0.7kg / 重量: 0.7kg

专利新品
New patented product



DL-1232-8-3

- Manual expander with rotating heads
旋转头扩管器
- Specification: $\Phi 16, 20, 25, 32\text{mm}$ and $\Phi 1/2'', 3/4'', 1''$
适用规格: 英制 $\Phi 1/2'', 3/4'', 1''$, 公制 $\Phi 16, 20, 25, 32\text{mm}$
- The expanding head can rotate automatically when expanding, then the wall of pipe will be well-distributed and smooth after expanding.
扩管时扩管头可自动旋转, 扩管后管壁光滑均匀
- Weight: 1kg / 重量: 1kg



DL-1432-15

- Drawing clamp, application range: $\Phi 16, 20, 25, 32\text{mm}$ or $1/2'', 3/4'', 1''$ or other sizes
are customizable.
拔管钳, 适用规格: $16, 20, 25, 32\text{mm}$ 或 $1/2'', 3/4'', 1''$, 可定制尺寸
- Press the ring, then you can pull out the pipe quickly.
按压套(环), 可快速拔出管子
- Weight: 4.1kg / 重量: 4.1kg



A Specifications:
Φ12, 16, 20, 25mm

DL-1232-10

- Small expander
二片式扩管器
- It can expand the pipes quickly.
可快速扩涨管子
- Weight: 0.4kg / 重量: 0.4kg



Specifications:
Φ10 12 16 20mm B



A Specifications:
Φ12,16,20,25,32mm

DL-1232-11

- Small expander
二片式扩管器
- It can expand the pipes quickly.
可快速扩涨管子
- Weight: 0.45kg / 重量: 0.45kg



Specifications:
Φ16,20,25,32mm B



DL-1432-7

- Pipe bender for aluminum plastic pipe
铝塑管弯管器
- Specification: Φ16, 20, 25, 32mm
适用规格: Φ16, 20, 25, 32mm

It is suitable for aluminum plastic pipe and copper plastic pipe bending, and the angle can be bent to more than 90 degrees. Also it can keep the pipe's wall without damage and the shape of pipe not changing when bending.
适用于铝塑管、铜塑管弯管用。角度弯至超过90°且不用内外弹簧可使弯管处管壁不变形不损伤

Die casting aluminum alloy main body and nylon module, make the tool high strength, no fracture and light weight, easy to carry.
压铸铝合金工艺主体与尼龙模块, 使工具强度高不断裂且重量轻, 方便携带

- Weight: 1.5kg / 重量: 1.5kg



DL-1432-7-A



DL-1432-7-B

- Inner spring/Outer spring for bending the pipe
内/外弯管弹簧
- Special for the aluminium plastic pipe.
铝塑管专用
- Specification: Φ16, 20, 25, 32mm
适用规格: Φ16,20,25,32mm


DL-1232-9-A

- Aluminum Plastic Pipe Straightener with five rollers without sucker
五排轮铝塑管直管器无吸盘
- Specification: $\Phi 16, 20, 25, 32\text{mm}$
适用规格: $\Phi 16, 20, 25, 32\text{mm}$
- It is suitable for straightening the aluminum-plastic pipes and the shape of pipes
won't be changed after the straightening.
适用于铝塑管盘管拉直管子用, 直管后的管子美观不变形
- It is made of aluminum alloy, beautiful and practical.
采用合金铝型材定制, 美观大方实用


DL-1232-9-B

- Five Rollers with Sucker Aluminum Plastic Pipe Straightener
五排轮铝塑管直管器带吸盘
- Specification: $\Phi 16, 20, 25, 32\text{mm}$
适用规格: $\Phi 16, 20, 25, 32\text{mm}$
- It is suitable for straightening the aluminum-plastic pipes and the shape of pipes
won't be changed after the straightening.
适用于铝塑管盘管拉直管子用, 直管后的管子美观不变形
- It is made of aluminum alloy, beautiful and practical.
采用合金铝型材定制, 美观大方实用


DL-1232-9-C

- Eight Rollers with Sucker Aluminum Plastic Pipe Straightener
八排轮铝塑管直管器带吸盘
- Specification: $\Phi 16, 20, 25, 32\text{mm}$
适用规格: $\Phi 16, 20, 25, 32\text{mm}$
- It is suitable for straightening the aluminum-plastic pipes and the shape of pipes
won't be changed after the straightening.
适用于铝塑管盘管拉直管子用, 直管后的管子美观不变形
- It is made of aluminum alloy, beautiful and practical.
采用合金铝型材定制, 美观大方实用


DL-1232-9-D

- Eight Rollers Rust Proof Aluminum Plastic Pipe Straightener with Sucker
八排防锈铝塑管直管器带吸盘
- Specification: $\Phi 16, 20, 25, 32\text{mm}$
适用规格: $\Phi 16, 20, 25, 32\text{mm}$
- It is suitable for straightening the aluminum-plastic pipes and the shape of pipes
won't be changed after the straightening.
适用于铝塑管盘管拉直管子用, 直管后的管子美观不变形
- It is made of aluminum alloy, beautiful and practical.
采用合金铝型材定制, 美观大方实用



DL-1232-21-A

European standard

- Staple Gun Tacker
卡钉枪（辅地暖管用）
- Specification: $\Phi 16, 20\text{mm}$ (Length: 4cm and 6cm)
适用规格：欧标通用（包括长度4cm和6cm的卡钉）
- It can be used standing to reduce the labor intensity and speed up when working.
可以站直使用，减轻安装工劳动强度且速度快
- Weight: 2.3kg / 重量：2.3kg

专利新品
New patented product



DL-1232-21-B

- Staple Gun Tacker
卡钉枪（辅地暖管用）
- Specification: $\Phi 16, 20\text{mm}$ (Length: 4cm and 6cm)
适用规格：欧标通用（包括长度4cm和6cm的卡钉）
- The main frame is made of nylon and aluminum, which is more lighter
主架采用尼龙和铝材质，重量更轻
- It can be used standing to reduce the labor intensity and speed up when working.
可以站直使用，减轻安装工劳动强度且速度快
- Weight: 1.3kg / 重量：1.3kg



DL-1232-21-C

Chinese standard

- Staple Gun Tacker
卡钉枪（辅地暖管用）
- Specification: $\Phi 16, 20\text{mm}$
适用规格：16, 20mm（国内标准）
- It can be used standing to reduce the labor intensity and speed up when working.
可以站直使用，减轻安装工劳动强度且速度快
- Weight: 2.3kg / 重量：2.3kg



DL-1232-21-1

- Plastic Tacker Pipe Clips
卡钉
- Specification: $\Phi 16, 20\text{mm}$ (Length: 4cm and 6cm)
适用规格：欧标通用（包括长度4cm和6cm的卡钉）





DL-1232-21-2

- Bending press tool for pex pipe
弯管片
- It is used for fixing the pex pipe after bending it.
PEX管弯管后固定(定位)用
- Specification: $\Phi 16, 20, 25, 32\text{mm}$
适用规格: $\Phi 16, 20, 25, 32\text{mm}$



DL-1232-21-3

- Clips
管卡
- There are steel screw and self-tapping screw which are used for fixing the pipe.
固定管子(定位)用, 有钢钉和自攻螺钉
- Specification: $\Phi 16, 20\text{mm}$
适用规格: $\Phi 16, 20\text{mm}$



DL-1232-13

- Triangle chamfer(internal and external) for the aluminium plastic pipe
三角整圆倒角器
- Specification: (1) $\Phi 16, 20, 25\text{mm}$, (2) $\Phi 20, 25, 32\text{mm}$
适用规格有二款: (1)16-20-25mm, (2)20-25-32mm
- The aluminum plastic pipe can be chamfered inside and outside together by the whole circle, so that the pipe can be inserted into the pipe fitting without breaking the seal ring.
用于铝塑管内外倒角, 便于管子插入管件内, 不损坏密封圈



DL-1232-14

- Internal chamfer
四合一整圆倒角器
- Specification for aluminium plastic pipe: $\Phi 16, 20, 25(26), 32\text{mm}$ or other sizes can be customized.
铝塑管专用规格有: $\Phi 16, 20, 25(26), 32\text{mm}$, 也可定制其他尺寸
- The material is steel and heat-treated, the edges for chamfering are durable to use, and one set of four specifications together is convenient to carry.
钢制产品经过热处理, 倒角刀口经久耐用, 四个规格集一把, 携带方便
- The aluminum plastic pipe can be chamfered inside by the whole circle, so that the pipe can be inserted into the pipe fittings without breaking the seal ring.
整圆管子和内倒角后便于管子插入管件内, 不损坏密封圈, 是目前热销品

DL-1232-15

专利新品
New patented product



- Internal chamfer
四合一整圆倒角器
- The handle can rotate automatically
手柄有自动旋转功能
- Specification for aluminium plastic pipe: $\Phi 16, 20, 25(26), 32\text{mm}$ or other sizes can be customized.
铝塑管专用规格: 16, 20, 25(26), 32mm, 也可定制其他尺寸
- The material is steel and heat-treated, the edges for chamfering are durable to use, and one set of four specifications together is convenient to carry.
钢制产品经过热处理, 倒角刀口经久耐用, 四个规格集一把, 携带方便
- The aluminum plastic pipe can be chamfered inside by the whole circle, so that the pipe can be inserted into the pipe fittings without breaking the seal ring.
整圆管子和内倒角后便于管子插入管件内, 不损坏密封圈, 是目前热销品

DL-1232-16

- External chamfer device
外倒角器
- Specification: $\Phi 16, 20, 25, 32\text{mm}$
适用规格: $\Phi 16, 20, 25, 32\text{mm}$
- The pipes can be only chamfered external, one piece one size.
只能倒管子外角, 一个规格一把





DL-1232-17

- Chamfering device for aluminium plastic pipe
单规格整圆倒角器
- Specification: $\Phi 16, 20, 25, 32\text{mm}$
适用规格: $\Phi 16, 20, 25, 32\text{mm}$
- The pipes can be chamfered both internal and external, one piece one size.
有内外倒角, 一个规格一把

DL-1232-18

- Chamfer for big size pipes
大口径整圆倒角器
- Specification: $\Phi 40, 50, 63\text{mm}$
适用规格: $\Phi 40, 50, 63\text{mm}$
- The material is steel and heat-treated, the edges for chamfering are durable to use.
钢制产品经过热处理, 倒角刀口经久耐用



DL-1432-1A

- TH Type Mold
TH型模块
- Specification: $\Phi 16, 20, 25(26), 32\text{mm}$
适用规格: $\Phi 16, 20, 25(26), 32\text{mm}$
- It is suitable for use in tools of DL-1432 and DL-1432-9.
适用于编号DL-1432和DL-1432-9二种工具



DL-1432-1B

- U Type Mold
U型模块
- Specification: $\Phi 14, 16, 18, 20, 25(26), 32\text{mm}$
适用规格: $\Phi 14, 16, 18, 20, 25(26), 32\text{mm}$
- It is suitable for use in tools of DL-1432 and DL-1432-9.
适用于编号DL-1432和DL-1432-9二种工具

DL-1432-1C

- RF Type Mold
RF型模块
- Specification: $\Phi 16, 20, 25, 32\text{mm}$
适用规格: $\Phi 16, 20, 25, 32\text{mm}$
- It is suitable for use in tools of DL-1432 and DL-1432-9.
适用于编号DL-1432和DL-1432-9二种工具



DL-1432-1D

- B Type Mold
B型模块
- Specification: $\Phi 16, 20, 25, 32\text{mm}$
适用规格: $\Phi 16, 20, 26, 32\text{mm}$
- It is suitable for use in tools of DL-1432 and DL-1432-9.
适用于编号DL-1432和DL-1432-9二种工具


DL-1432-1E

- V Type Mold
V型模块
- Specification: $\Phi 1/2, 3/4, 1"$ $\Phi 12, 14, 16, 18, 22, 28\text{mm}$
适用规格: $\Phi 1/2, 3/4, 1"$ $\Phi 12, 14, 16, 18, 22, 28\text{mm}$
- It is suitable for use in tools of DL-1432-A
适用于编号DL-1432-A


DL-1432-2-1A

- U Type Mold
U型模块
- Specification: $\Phi 14, 16, 18, 20, 25(26), 32\text{mm}$
适用规格: $\Phi 14, 16, 18, 20, 25(26), 32\text{mm}$
- It is suitable for use in tools of DL-1432-2, DL-1432-8, DL-4063, and DL-4063-C.
适用于编号DL-1432-2和DL-1432-8, DL-4063, DL-4063-C四种工具


DL-1432-2-1B

- TH Type Mold
TH型模块
- Specification: $\Phi 16, 20, 25, 32\text{mm}$
适用规格: $\Phi 16, 20, 25(26), 32\text{mm}$
- It is suitable for use in tools of DL-1432 and DL-1432-8.
适用于编号DL-1432-2和DL-1432-8二种工具


DL-4063-1E

- U Type Mold
大口径U型模块
- Specification: $\Phi 40, 50, 63, 75\text{mm}$
适用规格: $\Phi 40, 50, 63, 75\text{mm}$
- It is suitable for use in tool DL-4063 and 40, 50mm are also suitable for use in tool DL-4063-C.
适用于编号DL-4063, 大口径液压工具, 40, 50mm也适用于DL-4063-C电动卡压钳


 Curved shank expander
 16° taper, cap shape

 Straight shank expander
 20° taper, cap shape

DL-1232-A

- Expander heads for PEX pipe
纯塑管欧标尺寸扩管头
- They are suitable for Rehau, TECE, Watts, PRINTO pipes.
(瑞好款式). (TECE). (沃茨). (普林多)管子通用
- Specification: $16 \times 2.2, 20 \times 2.8, 25 \times 3.5, 32 \times 4.4$
适用规格: $16 \times 2.2, 20 \times 2.8, 25 \times 3.5, 32 \times 4.4$
- Straight handle expander with 20 degrees, the shape of cap is like the above picture.
直柄扩管器20°锥度, 帽的形状(如图)
- Curved handle expander with 18 degrees, the shape of cap is like the above picture.
弯柄扩管器18°锥度, 帽的形状(如图)


DL-1232-B

- 16&20mm together expander head
16&20连体扩管头
- There are two sizes on one expander head which is easy to carry.
一个扩管头上有二种规格，便于携带
- Specification: 16×2.2, 20×2.8, the other size also can be customized.
适用规格: 16×2.2, 20×2.8, 可以根据需求定制尺寸


DL-1232-C

- S5 series expander head for PEX pipe
S5系列纯塑扩管头
- Specification: 16×2.0(1.8), 20×2.0(1.9), 25×2.3, 32×2.9
适用规格: 16×2.0(1.8), 20×2.0(1.9), 25×2.3, 32×2.9


DL-1232-D

- Expander head for aluminium plastic pipe(gas pipe)
铝塑管(煤气管)扩管头(国外尺寸)
- Specification: 16.2×2.6, 20×2.9, 25×3.7, 32×4.7
适用规格: 16.2×2.6, 20×2.9, 25×3.7, 32×4.7


DL-1232-E

- Expander heads for aluminium plastic pipe
滑紧件铝塑管扩管头(国内尺寸)
- Specification: 16×2.2(2.3), 20×2.8, 25×3.5, 32×4.4
适用规格: 16×2.2(2.3), 20×2.8, 25×3.5, 32×4.4


DL-1232-F

- Expander heads for Uponor and Giacomini pipes
快插式扩管头
- There are two sizes in metric system and British system (American Standard), and also suitable for European standard thickening pipes.
有公制与英制(美标)二种尺寸, 还有欧标加厚管
- Metric system(Uponor): 16×2.0(1.8), 20×2.0(1.9), 25×2.3, 32×2.9
公制(欧博诺): 16×2.0(1.8), 20×2.0(1.9), 25×2.3, 32×2.9
- American Standard Specification: 1/2, 3/4, 1"
美标规格: 1/2, 3/4, 1"
- Thickening tube (Giacomini): 16×2.2, 20×2.8, 25×3.5, 32×4.4
加厚管(嘉科米尼): 16×2.2, 20×2.8, 25×3.5, 32×4.4
- This is for manual expander but not electric expander.
电动扩管器与手动扩管器工具的扩管头不可通用



Electric gear Manual plane



DL-1232-19

- Plastic pipe cutter
塑料快剪
- Range of application: 16-25mm pipes
剪管范围: 16-25mm
- It is suitable for cutting the PEX pipe.
较适合剪纯塑管




DL-1232-20

- Pipe cutter with aluminium alloy handle
快剪 (铝合金手柄)
- Range of application: 16-32mm pipes
剪管范围: 16-32mm
- It is suitable for cutting both the aluminium plastic pipe and the PEX pipe.
纯塑管、铝塑管都可以



DL-1232-21

- Pipe cutter with aluminium alloy handle
快剪 (铝合金手柄)
- Range of application: 16-32mm pipes
剪管范围: 16-32mm
- It is suitable for cutting both the aluminium plastic pipe and the PEX pipe.
纯塑管、铝塑管都可以



DL-1232-22

- Pipe cutter
管剪
- Range of application: 16-32mm pipes
剪管范围: 16-32mm
- It is suitable for cutting both the aluminium plastic pipe and the PEX pipe.
纯塑管、铝塑管都可以

DL-1232-23

- Hydraulic Test Pump
试压泵
- It is used for checking the quality of installation and whether the pressure test is leak or not after the completion of the water pipe installation.
水管安装完工后, 加压测试是否漏水, 检测安装质量



DL-1232-24

- Caliper gauge
卡规
- It is used for testing if the pipe fittings are installed perfectly after the installation, if it can be put in then they are seen as qualified installation, otherwise they are deemed to be unqualified and need to be reinstalled.
卡压管件安装完后用卡规测试是否能卡进去, 放得进去为安装合格, 否则视为不合格需重新安装

